

Audio kabely

Inakustik Reference NF-1203




Four high-speed signal conductors provide the signal transport for the NF- 1203. The DUO-PE II insulation and the air-filled PE tubes reduce undesired capacitance. The GAP II screening of the NF-1203 consists of lacquerinsulated wires. It prevents the formation of interfering eddy currents. The PE network jacket also prevents micro-vibrations. Another highlight is the solid Reference XLR plugs, which round out the two-way symmetry of this connection. As with the NF-1603, the NF-1203 is available either with GAP II cinch plugs or as an XLR version.

KEY-FEATURES

- ⊗ Doublesymmetrical design
- ⊗ DUO-PE II insulation
- ⊗ 3-fold PE-Tube insulation
- ⊗ GAP II screening
- ⊗ PE-Network Jacket
- ⊗ High Speed signal conductor

STANDARD



HIGH SPEED



AWARDS

To provide an impressive demonstration of the first-class precision of our Referenz Selection, we refined the Referenz Sound Edition Vol. 1 and Vol. 2 using what is known as RESO mastering. The new high-definition procedure provides significant acoustic improvements in terms of transparency, dynamics, bass reproduction and bass response.

The music is instilled with more atmosphere and emotion. And to transport this musical experience accordingly, it is not a common CD that is the sound storage material, but instead an HQCD, and instead of common LP vinyl, 180 g Audiophile Virgin Vinyl is used. In short: the highest quality to meet the highest standards.

